Data Sheet

We make sure

FUJITSU COMPUTERS SIEMENS

SCENICVIEW E22W-1

22 Inch LCD widescreen Display

Issue April 2007

Pages 2

An attractive price doesn't mean that you have to compromise on style or performance. The SCENICVIEW E22W-1 widescreen display offers best performance for the office and multimedia. With its slim and stylish design, the SCENICVIEW E22W-1 fits perfectly into your office environment.

Highlights

- 22-inch widescreen display for a perfect viewing experience at high resolution
- Best performance to an affordable price
- Very easy and comfortable to use
  - Plug & Play
  - Auto-adjust
  - Easy-to-use OSD menu

Ergonomics

- Optimum flicker-free and distortion-free picture
- Excellent colour purity
- Well balanced brightness uniformity
- Excellent high contrast (800:1)
- Space saving design

Technical highlights

- 22” (55.9 cm) LCD widescreen display
- Excellent contrast 800:1
- Brightness 300 cd/m^2
- Fast response time (typ.) 5 ms
- Internal power supply

Reliability

- Low power consumption
- Power management according to EPA
- Guaranteed quality and stability

Visible screen diagonal	22 inch (55.9 cm)
Resolutions	
Pixels	1680 x 1050
Pixels*	1280 x 768
* expanded	
Picture size	473.76 x 296.1 mm
Colours	16.7 million
Pixel Pitch	0.282 mm
Frequencies	
Horizontal	31 - 83 kHz
Vertical	56 - 76 Hz
Brightness (typical)	300 cd/m²
Contrast (typical)	800:1
Viewing angle (typical)	
Horizontal	160°
Vertical	160°
Response time (typical)	5 ms
Plug and Play	VESA DDC2B

Setting options
Brightness (Back light control)
Contrast, Volume control
Picture position (horizontal and vertical), H-size, Phase,
Color temperature and individual color setting
Auto-adjust (direct access key)
Activate factory settings
Menu language

OSD Language
English, German, Spanish, French, Italian, Russian, Polish, Dutch

Base	
Tilt angle	-5°/ +20°
Audio characteristics	
Audio signal input	3.5mm stereo phone jack
Audio output	1 W (L) + 1 W (R)

Electrical values (internal power supply)	
Rated voltage	100 - 230 V
Frequency	50 - 60 Hz
Power draw	
Max.	<55 W
Stand by	< 2 W
Protection class	1
Temperatures/ dimensions/ weight	
Ambient temperature (to IEC721):	
Working (recommended)	5°C to 35°C
Storage	-20°C to 60°C
Dimensions (H x W x D):	
(with stand)	514 x 418 x 219 mm
Weight (Monitor only)	5.4 kg
Reliability	
MTBF (demonstrated)	70,000 h
Lifetime of LCD backlight (brightness > 50 % of original brightness)	50,000 h
Compliance with standards	
Product safety	EN60950
Ergonomics	GS mark ISO13406-2 (Pixel fault class II)
Radiation immunity and RFI suppression	CE certification according to EC Directive 89/336/EEC (EN55022/B, EN55024 EN61000-3-2/-3); TCO'03
Video input	1 x D-SUB, 1 x DVI-D
Accessories	
1 x Power cable (1.5 m)*	1 x wall socket (Euro-Schuko-Type CEE7)
Data cable (1.5 m)*	D-SUB (15-pin)
Audio cable (1.8 m)*	3.5mm stereo phone jack
* detachable on display	
Special features	Standardized mounting interface according VESA FPMPMI (100 mm) Kensington Lock
Order code	S26361-K1200-V376 EAN: 4333643067144

All rights, including rights created by patent grant or registration of a utility model or design as well as rights of technical modifications are reserved. Delivery subject to availability. Designations may be trademarks, the use of which by third parties for their own purposes may violate the rights of the trademark owners.

Copyright © Fujitsu Siemens Computers, 05/2006

Published by

Fujitsu Siemens Computers
http://www.fujitsu-siemens.com/

Company stamp